



## DESCRIPTION

### General

Upgrade your **BMW iDrive CCC** with a 8.8 inch High resolution capacitive touch screen without replacing the original iDrive system. The VividScreen has the same design as the OEM iDrive Professional display, to maintain the OEM look.



### Example video

### Features

- LVDS input with touch screen support (NAVplay or CARplay)
- HDMI input (for Mirrorlink or Apple TV)
- Audio/Video input
- Rear camera input
- Dynamic Parking Lines (IPAS)
- Picture in Picture from Parking sensors (PiP)
- Front camera input
- 1280x480 Resolution
- FM Audio Transmission output
- Use OEM iDrive button to enter screen inputs
- 2 Year warranty & Support



## EXCLUSIVE INTERFACE FEATURES

### Features:

- 2\* AV input
- Audio output select
- Image retention while driving
- Adjustable parking lines via OSD menu
- Activation interface via original iDrive buttons
- OSD menu



## NOTES

- It is essential to have an Aux-in
- We recommend that the installation will be performed by a qualified specialist
- Check the other tabs for "Compatibility" - "Package contents" - "Product specifications"



## COMPATIBILITY

---

### CAR

This kit is compatible with the following models:

### BMW

3 serie (E90/E91/E92/E93) 2005-2009 iDrive CCC Professional & Business (6.5" & 8.8")

5 serie (E60/E61) 2003-2009 iDrive CCC Professional & Business (6.5" & 8.8")

6 serie (E63/E64) 2004-2009 iDrive CCC Professional & Business (6.5" & 8.8")

\*Picture in picture option only compatible with 8.8" iDrive screen.

\*Rear select via CAN-BUS only available with automatic gearbox

\*For manual gear please use CAN-BUS interface for reverse gear signal.

## REQUIREMENT

---

<b>AUDIO OUTPUT</b>	The interface inserts ONLY video signals into the infotainment. It is essential to have an Aux-in, when using audio from an external AV source.
<b>CVBS</b>	Only compatible with NTSC sources.
<b>LVDS</b>	LVDS input is compatible with NAVplay & CARplay module
<b>SCREEN</b>	Interface is compatible with 6.5" & 8.8"
<b>FRONT CAMERA</b>	The front camera input will automatically switch after leaving the reverse gear. You can set the display time in seconds via the OSD menu (1-15 sec). It is also possible to select the FRONT camera input manually
<b>OEM REAR CAMERA</b>	The interface does not switch back automatically to the OEM rear camera input when the reverse gear is engaged.
<b>GUIDELINES</b>	iPAS & Static lines are available via the interface OSD menu
<b>PIP</b>	We recommend that the installation will be performed by a qualified specialist
<b>REAR SELECT CAMERA INPUT</b>	Interface will respond on CAN for cars with auto gearbox. When manual gear box please use the rear detection wire.
<b>INSTALLATION</b>	We recommend that the installation will be performed by a qualified specialist