



DESCRIPTION

General

5" monitor with two camera inputs with two different brackets to install the camera.

The screen will switch ON automatically when it receivece a video signal. If there's no signal, the monitor saves power by shutting itself off automatically.

Features

- 5" High resolution display
- Resolution 800 x 480 pixels
- PAL & NTSC auto switch
- Dual view input (2* camera inputs)
- Auto video detection
- Sunshade
- 2* types of mounting brackets
- CE-mark:
- 2 Year warranty & Support

EXCLUSIVE CAMERA FEATURES

Sunshade

Sunshade

Mounting bracket

Two types of mounting bracket:

- 1: Standard bracket
- 2: Glass mount bracket

OSD Menu

The menu functions can be adjusted using the + and - buttons on the backside of the monitor:

Brightness:	Adjust the brightness level of the screen between 0 and 100.
Contrast:	Adjust the contrast of the screen between 0 and 100.
Colour:	Adjust the colour of the screen between 0 and 100.
Hue:	Adjust the hue of the screen between 0 and 100.
Language:	English / Chinese
Reset	Resets the unit to factory settings

NOTES

- We recommend that the installation will be performed by a qualified specialist
- Check also the other tabs for "Compatibility" - "Package contents" - "Product specifications"

LEGAL NOTICE

Please check before purchase if it is aloud to install this camera and it wont affect your MOT.