

Rear & Front camera interface Mercedes Vito Audio30_40 (Garmin)

Art. Nr: IF-MB-AU30V





DESCRIPTION

General

The NavInc NAVconnect interfaces allow for connecting video sources to the original Mercedes Vito Audio 30 40 (Garmin)

The interface is equipped with various options such as; 1* Front camera input - 1* Rear camera input & LVDS input

Features

- 1x Rear camera input
- 1x Front camera input (with auto switch OFF)
- 1x LVDS input (to connect APPplay & NAVplay)
- Adjustubele parking lines via OSD menu
- OEM button support
- 3 Year warranty & Support

EXCLUSIVE INTERFACE FEATURES

Features:

- Reverse Camera input
- Front camera input
- Image retention while driving
- Adjustable parking lines
- OSD menu

OEM BUTTON



	Button	Operation	Function
AUDIO30 AUDIO40	НОМЕ	Long Press	Mode switch
	NAVI/MAP	Long Press	Mode switch

CAMERA FEATURES

Rear camera input with Parking guidelines

Rear camera input with parking guidleines option.

The guidelines makes it much easier to determine the distance to the object you are driving towards.

The guidelines are adjustable horizontal as well as vertical so the lines can be adjusted to the car.





Ajustable guide lines

Front camera input

Front camera input which will be selected after leaving the reverse gear. Via the OSD menu you can select show time:

3 sec

5 sec

10 sec

15 sec

NOTES

- We recommend that the installation will be performed by a qualified specialist
- Check the other tabs for "Compatibility" "Package contents" "Product specifications"

LEGAL INFORMATION

The driver ofthe vehicle should not be inferred from the motion images. In many countries, watching movies while driving is prohibited. Therefore we accept no responsibility for material or personal injuries, directly or indirectly, due to installation of the interface modules.

Interface and Software basic information:

The NavInc interfaces are no navigation systems or screens to replace the navigation system. The NavInc interfaces enable the possibilities to connect different Audio/Video sources to the navigation system.

Manufacturers create adjusted software and hardware versions, options and enhancements which ensures that the compatibility of the products cannot be guaranteed 100%. Compatibility lists are based on customer feedback and experiences and will constantly be updated for optimal customer support.



COMPATIBILITY

CAR

This kit is compatible with the following models:

Mercedes Vito - Audio30 (Garmin) Mercedes Vito - Audio40 (Garmin) (Not compatible with Pioneer head-units)



AUDIO 40 (Pioneer)



AUDIO 30 (Garmin)

REQUIREMENT

	The interface inserts ONLY video signals into the infotainment. It is essential to		
	have an Aux-in, when using audio from an external AV source.		
VBS	Only compatible with NTSC sources.		
VDS	Compatible with NAVplay & APPplay module		
	Interface is compatible with Audio30 & Audio40 from Garmin only (not Pioneer)		
	The front camera input will automatically switch after leaving the reverse gear.		
RONT CAMERA	You can set the display time in seconds via the OSD menu (1-15 sec).		
	It is also possible to select the FRONT camera input manually		
EM REAR	The interface does switch back automatically to the OEM rear camera input		
AMERA	when the reverse gear is engaged.		
UIDELINES	Static lines are available via the interface OSD menu		
PAS	iPAS option is not available (moveable grid lines)		
IP	PiP option is not available for original parking sensor overlay (Picture in Picture)		
EAR SELECT	When interface only work with the 121/ reverse detection wire (gray wire)		
AMERA INPUT	which interface only work with the 12v reverse detection whe (grey whe)		
NSTALLATION	We recommend that the installation will be performed by a qualified specialist		
ОТЕ	Support multi-touch for NAVplay		
EM REAR AMERA EUIDELINES PAS IP EAR SELECT AMERA INPUT	The interface does switch back automatically to the OEM rear camera input when the reverse gear is engaged. Static lines are available via the interface OSD menu iPAS option is not available (moveable grid lines) PIP option is not available for original parking sensor overlay (Picture in Picture When interface only work with the 12V reverse detection wire (grey wire) We recommend that the installation will be performed by a qualified specialist		