

## **Multimedia interface for MMI High 2G systems**

**Art. Nr:** IF-AUDI-2G

---

### **General**

The NavInc interfaces allow for connecting audio/video sources to the original navigation system of Audi.

The interface ensures that an input is created on the original navigation system, on which various external video sources can be connected (e.g. DVD player, DVB-T TV, iPod, reversing camera, external navigation systems, etc.). The images will be displayed on the navigation screen. The audio of the audio/video source will be send via an audio interface to the original system.

### **Features:**

- RGB input (Connecting external navigation system)
- 2x Audio/Video input (connect video sources, TV / DVD / iPod)
- Camera input (connecting reversing camera)
- 2x Video output (connect headrest screens)
- NTSC support
- Audio interface via MOST
- Image retention while driving
- Adjustable parking lines
- CE-approved

### **OSD menu**

Through the interface menu, various settings can be adjusted for optimal image, namely;

- Tint
- Brightness
- Contrast
- Sharpness
- Display position

### **Camera function**

Via the camera input of the interface an aftermarket camera system can be connected to the navigation system. The camera image will be displayed automatically on the screen when the car is put in the reverse gear.

### **Parking guidelines**

In the camera image on screen parking guidelines can be displayed. This makes it much easier to determine the distance to the object you are driving towards. The guidelines are adjustable horizontal as well as vertical so the lines can be adjusted to the car.



**Adjustable guide lines**

### **Video output**

The video output connection can be used for linking headrest monitors or roof monitors. Sources connected to the interface will also be shown on the screens in the back.

#### **The following is provided in the set:**

- NavInc AV-interface IF-AUDI-2G
- Installation- and user manual
- Warranty
- Invoice

#### **Product specifications**

Voltage: 12V – 24V DC

Voltage-operating capacity: 8 – 18V DC

Standby current: 0 mA

Operating current: 5 Watt max.

Power input: 12V

Temperature range: - 30°C up to + 80°C

Weight: 250grs

Dimensions(W x H x D): 130 x 20 x 102mm

#### **Additional information:**

- Check at the tab “compatibility” on top of this page if your radio or navigation system is suitable for this product.
- No constant voltage needed (+30) therefore the interface is much more stable.
- “Mute” function for the video inputs which are not used.
- Use of a metal casing and new components (not Chinese or remanufactured components).
- Not possible to control by MMI controls
- Plug and play cable set

#### **Legal information:**

The driver of the vehicle should not be inferred from the motion images. In many countries, watching movies while driving is prohibited. Therefore we accept no responsibility for material or personal injuries, directly or indirectly, due to installation of the interface modules.

#### **Interface and Software basic information:**

The NavInc interfaces are no navigation systems or screens to replace the navigation system. The NavInc interfaces enable the possibilities to connect different Audio/Video sources to the navigation system.

Manufacturers create adjusted software and hardware versions, options and enhancements which ensures that the compatibility of the products cannot be guaranteed 100%. Compatibility lists are based on customer feedback and experiences and will constantly be updated for optimal customer support.

The functioning of the interfaces may be influenced by software updates from the manufacturer/dealers. In such cases we will provide a software update for this interfaces (not applicable for all products) within one year after invoice date. The costs for (de)-installation of the interface must be paid by the customer and the interface must be supplied to us.

Car manufacturers create adjusted versions of software and updates without having informed third parties about it. We therefore recommend to not update the car if not necessary.

In exceptional cases it is possible that the interface is not accepted by the vehicle,

even after replacing the interface or software updates. In such cases, we should looking for an alternative.

**Compatible with the following Audi models:**

A4 (B8/8K)	2007-2009
A5 (B8)	2007-2009
A6 (4F)	2004-2009
A8 (4E)	2002-2009
Q7 (4L)	2006-2009

**Remarks:**

- Only in combination with MMI 2G system
- Installation also possible in combination with original DVB-T tuner
- Installation not possible in combination with double 6 CD changer
- Installation not possible in combination with Dension Gateway 500
- Installation also possible in combination with original reversing camera
- Not possible to control by MMI controls

**Images of suitable navigation systems:**

**A4**



**A5**



**A6**



**A8**



**Not suitable for the following models/system:**

- MMI Basic plus
- RNS-E
- MMI 3G