

Multimedia video interface Audi Etron/A6/A7/A8/Golf8/ID3

Art. Nr: IF-AUDI-7GPV



DESCRIPTION

General

The NavInc NAVconnect interfaces allow for connecting video sources to the original VAG MIB3 systems (8.8" & 10").

The interface is equipped with various options such as; 1* LVDS input, 1* Front camera input & 1* Rear camera input.

Example video

Features

- 1x Rear camera input
- 1x Front camera input (with auto switch OFF)
- 1x LVDS input
- 2x HDMI input (optional)
- Adjustable parking lines via OSD menu
- iPAS (moveable grid lines)
- 3 Year warranty & Support

EXCLUSIVE INTERFACE FEATURES



Rear camera
input



Front camera
input



iPAS
moveable gridlines



Grid
gridlines



Audio/video input
CVBS - input



OEM button
control

Features:

- OEM button support
- Rear camera input (CVBS - NTSC)
- iPAS lines (moveable grid lines)
- Front camera input (CVBS - NTSC)
- Time delay setting front camera input (3-15sec)
- OSD menu (to adjust interface settings)

NAVconnect OEM Button



	Button	Operation	Function
MIB3	RETURN	Long Press	Mode switch

CAMERA FEATURES

Rear camera input with Parking guidelines

Rear camera input with parking guidleines option.

The guidelines makes it much easier to determine the distance to the object you are driving towards.

The guidelines are adjustable horizontal as well as vertical so the lines can be adjusted to the car.



Ajustable guide lines

Front camera input

Front camera input which will be selected after leaving the reverse gear.



Via the OSD menu you can select show time:

- 3 sec
- 5 sec
- 10 sec
- 15 sec

Camera modes

It is possible to adjust the camera mode in Type 1 & Type 2



	REMOTE	SETTING	Function
MIB3		TYPE 1	Full screen (rear & front camera mode)
		TYPE 2	4:3 screen (rear & front camera mode)

NOTES

-
- We recommend that the installation will be performed by a qualified specialist

- Check the other tabs for "Compatibility" - "Package contents" - "Product specifications"

LEGAL INFORMATION

The driver of the vehicle should not be inferred from the motion images. In many countries, watching movies while driving is prohibited. Therefore we accept no responsibility for material or personal injuries, directly or indirectly, due to installation of the interface modules.

Interface and Software basic information:

The NavInc interfaces are no navigation systems or screens to replace the navigation system. The NavInc interfaces enable the possibilities to connect different Audio/Video sources to the navigation system.

Manufacturers create adjusted software and hardware versions, options and enhancements which ensures that the compatibility of the products cannot be guaranteed 100%. Compatibility lists are based on customer feedback and experiences and will constantly be updated for optimal customer support.



COMPATIBILITY

CAR

This kit is compatible with the following models:

NOTE

AUDIO OUTPUT	The interface inserts ONLY video signals into the infotainment. It is essential to have an Aux-in, when using audio from an external AV source.
CVBS	Only compatible with NTSC sources.

LVDS	Compatible with NAVplay & APPplay module
SCREEN	Interface is compatible with VAG – 8.8” & 10”
FRONT CAMERA	<p>The front camera input will automatically switch after leaving the reverse gear.</p> <p>You can set the display time in seconds via the OSD menu (1-15 sec).</p> <p>It is also possible to select the FRONT camera input manually</p>
OEM REAR CAMERA	The interface does not switch back automatically to the OEM rear camera input when the reverse gear is engaged.
GUIDELINES	iPAS & Static lines are available via the interface OSD menu
iPAS	iPAS option is available (moveable grid lines)
PIP	PiP option is available for original parking sensor overlay (Picture in Picture)
REAR SELECT CAMERA INPUT	When interface wont respond on reverse CAN, please use the 12V reverse detection wire (grey wire)
INSTALLATION	We recommend that the installation will be performed by a qualified specialist
NOTE	PiP function = splitscreen (FW210429>)

