

AHD Camera interface Audi & Porsche MIB3 (FDcan)

Art. Nr: RC-AUDI-7FD

DESCRIPTION

General

The NavInc NAVconnect interfaces allow for connecting video sources to the original VAG MIB3 head-unit.

The interface is equipped with various options such as; 1* Front camera input & 1* Rear camera input.

Features

- 1x Rear camera input
- 1x Front camera input (with auto switch OFF)
- AHD & CVBS support (PAL/NTSC)
- Split screen option (PiP)
- iPAS option (moveable grid lines)
- Adjustabele parking lines via OSD menu
- FD can chip
- 12V & 24V support
- 3 Year warranty & Support

NOTES

- We recommend that the installation will be performed by a qualified specialist
- Check the other tabs for "Compatibility" - "Package contents" - "Product specifications"

REQUIREMENTS

AUDIO OUTPUT	The interface inserts ONLY video signals into the infotainment. It is essential to have an Aux-in, when using audio from an external AV source.
CVBS	Only compatible with NTSC sources.
SCREEN	Interface is compatible with 8.8", 10.1", 12,3"& 15" MIB monitors
FRONT CAMERA	The front camera input will automatically switch after leaving the reverse gear. You can set the display time in seconds via the OSD menu (1-15 sec). It is also possible to select the FRONT camera input manually
OEM REAR CAMERA	The interface does not switch back automatically to the OEM rear camera input when the reverse gear is engaged.
GUIDELINES	iPAS & Static lines are available via the interface OSD menu
iPAS	iPAS option is available (moveable grid lines)
PIP	PiP option is available for original parking sensor overlay (Picture in Picture)
REAR SELECT CAMERA INPUT	When interface won't respond on reverse CAN, please use the 12V reverse detection wire (grey wire)
INSTALLATION	We recommend that the installation will be performed by a qualified specialist
NOTE	PiP function = splitscreen or Picture in Picture, depending on car model