



DESCRIPTION

General

The NavInc NAVconnect interfaces allow for connecting video sources to the original Skoda/Seat/Volkswagen head-unit (8.2").

The interface is equipped with various options such as; 1* Front camera input - 1* Rear camera input & LVDS input

Example video

Features

- 1x Rear camera input
- 1x Front camera input (with auto switch OFF)
- 1x LVDS input (to connect APPplay & NAVplay)
- Adjustable parking lines via OSD menu
- OEM button support
- 3 Year warranty & Support

EXCLUSIVE INTERFACE FEATURES

Features:

- Reverse Camera input
- Front camera input
- Image retention while driving
- Adjustable parking lines
- OSD menu

OEM BUTTON



	Button	Operation	Function
SKODA MIB3	MENU	Long Press	Mode switch

CAMERA FEATURES

Rear camera input with Parking guidelines

Rear camera input with parking guidelines option.

The guidelines makes it much easier to determine the distance to the object you are driving towards.

The guidelines are adjustable horizontal as well as vertical so the lines can be adjusted to the car.



Ajustable guide lines

Front camera input

Front camera input which will be selected after leaving the reverse gear.

Via the OSD menu you can select show time:

- 3 sec
- 5 sec
- 10 sec
- 15 sec

NOTES

- We recommend that the installation will be performed by a qualified specialist

- Check the other tabs for "Compatibility" - "Package contents" - "Product specifications"

LEGAL INFORMATION

The driver of the vehicle should not be inferred from the motion images. In many countries, watching movies while driving is prohibited. Therefore we accept no responsibility for material or personal injuries, directly or indirectly, due to installation of the interface modules.

Interface and Software basic information:

The NavInc interfaces are no navigation systems or screens to replace the navigation system. The NavInc interfaces enable the possibilities to connect different Audio/Video sources to the navigation system.

Manufacturers create adjusted software and hardware versions, options and enhancements which ensures that the compatibility of the products cannot be guaranteed 100%. Compatibility lists are based on customer feedback and experiences and will constantly be updated for optimal customer support.



COMPATIBILITY

CAR

This kit is compatible with the following models:

Skoda with MIB3 – Swing (8.0" & 8.25")

Seat with MIB3 – radio/media (8.0" & 8.25")

Volkswagen with MIB3 – Composition Media (8.0" & 8.25")

Note:

- We recommend that the installation will be performed by a qualified specialist

AUDIO OUTPUT	The interface inserts ONLY video signals into the infotainment.
CVBS	Only compatible with NTSC sources.
LVDS	Compatible with APPplay or NAVplay
SCREEN	Interface is compatible with (8.0" & 8.25")MIB3 monitors
FRONT CAMERA	The front camera input will automatically switch after leaving the reverse gear. You can set the display time in seconds via the OSD menu (1-15 sec).
OEM REAR CAMERA	x
GUIDELINES	Static lines are available via the interface OSD menu
iPAS	iPAS option is not available (moveable grid lines)
PIP	PiP option is not available for original parking sensor overlay (Picture in Picture)

REAR SELECT CAMERA INPUT	No CAN-BUS connection, use the 12V reverse detection wire (grey wire)
INSTALLATION	We recommend that the installation will be performed by a qualified specialist
NOTE	Must open the head-unit to install sub-board Not compatible with VW Caddy & Golf 8 --> must us RC-MIB3LTC